## 6MP Smart Hybrid Light Lite AI Fixed-Focal IPC



- 6MP 1/2.7" CMOS Sensor
- Support H.264+, H.265+
- IR Light: 40 m, White Light: 40m
- Support Perimeter Protection, SMD
- 2.8mm fixed lens (3.6mm optional)
- Built-in Mic(optional)
- 12 VDC/PoE power supply
- IP67 protection

Camera		
Image Sensor	1/2.7" CMOS	
Max. Resolution	6MP	
Scanning System	Progressive	
Electronic Shutter Speed	Auto/Manual 1/3 s-1/100,000 s	
Min. Illumination	0.006Lux(Illuminator off); 0Lux (Illuminator on)	
S/N Ratio	> 56 dB	
Illumination Distance	IR Light: 40 m, White Light: 40m	
Illuminator Control	Auto; Manual	
Lens		
Lens Type	Fixed-Focal	
Focal Length	2.8mm/3.6mm	
Max. Aperture	F1.6	
Iris Type	Auto	
Intelligence		
Smart Motion Detection	Yes	
Perimeter Protection	Intrusion, Tripwire (Support the classification of Vehicle, Human and Non-Motor)	
Al Search	Work together with NVR	
Video		
Compression	H.264H; H.264M; H.264B; H.265	
Video Frame Rate	Main Stream: 6MP (1 fps–25/30 fps)	
	Sub Stream: D1 (1 fps-25/30 fps)	
	Third Stream: 720P (1 fps-25/30 fps)	
Stream Capability	3 Streams	
Bit Rate Control	CBR/VBR	
Video Bit Rate	H.264: 3 Kbps-20480 Kbps	
	H.265: 3 Kbps-20480 Kbps	
Day/Night	Color/B/W	
BLC	Yes	

## Lite Al Series | IPC-BF2649S-S2

HLC	Yes
WDR	DWDR
White Balance	Yes
Gain Control	Auto/Manual
Noise Reduction	3D NR
Motion Detection	OFF/ON (4 Areas, rectangular)
Image Rotation	180°
Mirror	Yes
Privacy Masking	4 Areas
Audio	
Built-in Mic	NA (optional)
Alarm	
Alarm Event	Disconnection; IP Conflict; No SD Card; Capacity Warning; SD Card Error
Network	
Network	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network Protocol	TCP/IP;UDP;HTTP;DHCP;DDNS;FTP;UPNP
Interoperability	ONVIF; CGI; P2P(Optional)
Storage	SD Card (Optional)
Browser	IE: IE8 and later
Management Software	PC Software(SVMS)
Mobile Client	IOS; Android
Power	
Power Supply	12V DC (±30%)/PoE (802.3af)
Power Consumption	Max. 3W
Environment	
Operating Conditions	-30°C to +60°C (-22°F to +140°F)/Less than 95% RH
Storage Conditions	-40°C to +60°C (-40°F to +140°F)
Protection Grade	IP67
Structure	
Casing	Metal( pedestal: plastic )
Dimensions	70mm×70mmx170mm
Net Weight	420g